



## Specifications: Supreme Model

<b>Dimensions</b>	33.5"W x 29.5"H x 40.5"L <b>With Tower:</b> 42"W x 46.25"H x 40.5L"
<b>Door Swing</b>	Right Hand/Left Hand
<b>Tub construction</b>	Marine grade gel coat fiberglass with fire retardant properties
<b>Tower</b>	Fiberglass construction located on right hand side
<b>Tub surface</b>	"Kohler" white - CSA approved bath gel coat supported with fire retardant fiberglass
<b>Warranty</b>	*5 year warranty on fiberglass bathtub, door handle, and latching mechanism- 1 year parts and labor, remaining 4 years parts only. *One year warranty on hydrotherapy components, chemical dispenser, hand-held shower and drains *Lifetime warranty on door seal
<b>Approvals</b>	CSA  UL/ANSI
<b>Door clearance required</b>	Will fit through a 30.0" door - (28.0" with door jambs removed) with tower and chemical wash removed
<b>Length</b>	Door closed: 40.5" With drip tray: 44.5 " Door open: 63.5"
<b>Width</b>	33.5" <b>Width with Tower:</b> 42"
<b>Height</b>	29.5" <b>Height with Tower:</b> 46.25"
<b>Seat height</b>	14.5"
<b>Door opening width</b>	16.5"
<b>Step in height</b>	4.25"

<b>Faucet</b>	¾" Symmons valve with 2-way diverter Adjustable shower head with pause button
<b>Weight</b>	350 lbs
<b>Water Capacity</b>	25-30 gallons
<b>Door seal</b>	Extruded silicone rubber gasket
<b>Door lock</b>	Stainless steel cantilever mechanism
<b>Safety latch</b>	Stainless steel
<b>Hinges</b>	Stainless steel
<b>Access Panels</b>	Measures: 8" X 8" Located on 3 sides of the shroud Access is also possible from below the bathtub if on wood floor application
<b>Drain size</b>	1.5"
<b>Drain Location</b>	When viewed from outside the tub, drain is always on the right hand side
<b>Drain Waste &amp; Overflow Filler</b>	Geberit component – brass construction includes 1 way anti-siphoning valve
<b>Drain size (drip-tray)</b>	1.25" Includes one-way valve & chrome drain
<b>San Air System</b>	12 jet warm air
<b>Air Blower</b>	CSA, UL approved Model A - Air massage 9.5 A 120 V, 60 HZ
<b>Power Input</b>	110/120 V – 15A GFI outlet required for jetted tubs
<b>Piping</b>	PVC flex
<b>Sanitizing System</b>	Scald guard Moen taps, comprised of T&S brass components